

## Two Solid Swing Door CounterLine Remote

**Range:** BackBar

**SKOPE ID:** CL402S

**Dimensions:** 1580 mm (W) × 680 mm (D) × 830 mm (H)\*

**Capacity:** 345 L

\* Height with castors is adjustable from 820 to 835.

**Project:** \_\_\_\_\_

**Item #:** \_\_\_\_\_



A solid door under-bar fridge designed to merchandise ready-to-serve cold beverages and food in bars, restaurants, clubs, pubs, and cafés. With M1 compliance it is engineered to serve cold food and drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. This fridge is designed to be fitted to a remote refrigeration unit (supplied by others) running on R134a, R404A, or as specified at the time of order. The fridge comes fitted with a thermal expansion valve, solenoid valve, and ball valves. It has copper liquid and suction loops to be connected to the remote unit. Other valve options are available on order. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



**Warranty**




**GEMS**



**SKOPE-connect**





## Cabinet

Type	CounterLine		
Finish	Powdercoat galvanised steel or stainless steel		
Insulation	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)	
Doors	Type	Solid swing door ()	
	Opening Size	Height (mm)	538
		Width (mm)	511
Shelving	Four adjustable height plastic-coated wire shelves 4 × outer shelf (547W × 530D)		
Lighting*	1 × 16W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling		

## Dimensions†

	External	Internal	Packed
Width (mm)	1580	1120	TBC
Depth (mm)	680	565	TBC
Height (mm)	830 (std. castors)	545	TBC
	725 (plinth mount)		
Weight (kg)	160		TBC
Capacity (L)	345		
Footprint (m <sup>2</sup> )	1.07		

## Ventilation/Clearance (mm)

Take into account remote services location.

Top	Sides	Rear
Not required	Not required	Not required

## Product Loading

	Facing	Loading
330 ml can	32	256
600 ml bottle	28	196

## Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet	Multiple cabinets	
		At each joint	At each end wall
Less than 1 metre	±5 mm	±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm	-5 mm to +10 mm	+15 mm

## Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)	
Maximum Ambient Temperature (°C)	40	
Sound Level (dB(A))	Standard	< 60
	Hush Mode	< 60

## Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	n.a.
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	2.51 kWh/24 h
Annual Running Costs	\$275 (@ \$0.30/kWh)

## Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	1.9 m power cord with 3-pin, 10 amp plug
Current Draw (A)	2.0

## Remote Services

Location	Rear or base
Drain Size	OD 19 mm
Pipe Connection	Liquid line OD 6.35 mm Suction line OD 9.52 mm

## Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)		
System Type	Remote cartridge		
Cartridge Weight (kg)	16		
Refrigerant/Charge	Thermostatic expansion valve fitted to suit refrigerant (R134a or R404A standard)/Nitrogen holding charge		
Nominal Capacity (W)	n.a.		
Heat Rejection (W)	Average	n.a.	Peak n.a.
Remote Duty (W)	280		
Defrost Type	Automatic, off-cycle		



CL.2.SSW.r  
on the SKOPE website

\* Accessible via the free SKOPE-connect™ app.