20TSERIES



E23T3

Technical data sheet for

E23T3 ON THE SK23T STAND

Half Size Electric Convection Oven TOUCH SCREEN CONTROL on a Stainless Steel Stand





F23T3

Unit shall be a Moffat electrically heated Turbofan convection oven. The oven shall have a one piece vitreous enamel oven chamber, stainless top and sides and safe touch vented easy clean drop down door. Oven shall have capacity for three half size sheet pans. The oven shall have 2.8kW heating elements. The oven shall have a bi-directional single reversing fan system and feature a single halogen oven lamp. The oven shall feature a programmable Touch Screen menu controller. Oven shall be able to be bench mounted on 76mm feet or mounted on oven stand model SK23T. Oven shall be fitted with a 15A plug-in cordset. Unit shall be supplied in 100% recyclable shipping packaging.

SK23T

Unit shall be a Moffat Turbofan stainless steel oven stand. The stand shall be constructed from stainless steel tube with castors, with front castors having dual swivel and wheel locks. It shall be fitted with 6 tray runners suitable for half size sheet pans. The stand shall be fully compatible with, and support, Turbofan Convection Oven model E23T3. Unit shall be supplied in 100% recyclable shipping packaging.

STANDARD FEATURES

- 3 460mm x 330mm / 18" x 13" half size sheet pan capacity
- 3 GN 2/3 pan capacity
- 85mm tray spacing
- Compact 745mm width
- Touch Screen control
- Icon driven program menu
- USB port for program/icon updating
- Individual shelf timers
- Multi-stage programs
- Steam injection mode and manual injection
- Bi-directional reversing fan system
- 2.8kW heating
- 15A plug-in cordset fitted
- Vitreous enameled oven chamber
- Plug-in continuous oven door seal
- · Safe-Touch vented drop down door
- Stay-Cool door handle
- Heavy-duty door hinges
- Easy clean door glass system
- Halogen oven lamp
- Dia. 180mm full stainless steel oven fan
- Anti-skid 50mm dia. 76mm high adjustable stainless steel feet
- 3 oven wire racks supplied
- 100% recyclable packaging

ACCESSORIES

Turbofan SK23T Oven Stand



20TSERIES

turbofan

E23T3

E23T3 Half Size Electric Convection Oven TOUCH SCREEN CONTROL on a Stainless Steel Stand

CONSTRUCTION

Vitreous enameled fully welded oven chamber Stainless steel front, sides and top exterior Stainless steel oven fan baffle and oven vent Removable 3 position chrome plated wire side racks Oven racks chrome plated wire (3 supplied)

Stainless steel frame drop down hinged door

5mm thick door outer glass

5mm thick low energy loss door inner glass Heavy-duty counterbalanced door hinges Wear resistant powder coated welded door handle

Stainless steel control panel

Aluminised coated steel base and rear panels

CONTROLS

5.7" LED backlit touch screen Icon driven program menu

BMP image icon imports via USB port

Temperature range 50-260°C Individual shelf timers

Multi-stage programs

Over-temperature safety cut-out

CLEANING

Stainless steel top and sides continuous exterior panel

Vitreous enameled oven chamber

Fully removable chrome plated oven side racks

Removable stainless steel oven fan baffle

Full stainless steel oven fan

Easy clean door system with hinge out door inner glass

(no tools required)

Removable plug-in oven door seal (no tools required) 76mm high stainless steel feet for easy access underside

SPECIFICATIONS

Electrical Requirements

230-240V, 50Hz, 1P+N+E, 3kW, 12A

15A cordset fitted

Water Requirements (optional)

Cold water connection 34" BSP male

80psi maximum inlet pressure / 20psi minimum inlet pressure

External Dimensions

Width 745mm

Height 512mm including 76mm feet 643mm Depth

Oven Internal Dimensions Width 495mm 305mm Height Depth 340mm

0.51m3

Volume

Oven Rack Dimensions

Width 460mm

Depth 330mm

Nett Weight (E23T3)

Packing Data (E23T3)

54.6kg 0.36m3

Width 755mm 585mm Height Depth 810mm

SK23T Stainless Steel Stand

All stainless steel welded frame oven stand for Turbofan E23T3 Series oven

6 position tray runners standard

76mm diameter wheel swivel castors standard with 2 front castors with dual swivel and wheel

Welded 38mm and 32mm square tube front and rear frames Welded rack supports/side frames

4 dia. 76mm swivel castors with 2 front castors dual wheel and swivel lock

Top frame oven supports suit Turbofan E23T3 Series Oven

Supplied CKD for assembly on site

External Dimensions (SK23T Oven Stand)

Width 735mm Height 880mm Depth 530mm

Nett Weight (SK23T Oven Stand)

17kg

Packing Data (SK23T Oven Stand)

19kg 0.11m3

Width 765mm Height 900mm 152mm Depth

INSTALLATION CLEARANCES

Rear 25mm LH Side 25mm 25mm RH Side

CLEARANCE FROM SOURCES OF HEAT

A minimum distance of 300mm from the appliance sides is required

MOFFAT

Australia www.moffat.com.au New Zealand www.moffat.co.nz www.turbofanoven.com

Australia Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +61 3-9518 3888 Facsimile +61 3-9518 3833 vsales@moffat.com.au

New South Wales Telephone +61 2-8833 4111 nswsales@moffat.com.au

South Australia Telephone +61 3-9518 3888 vsales@moffat.com.au

Queensland Telephone +61 7-3630 8600 qldsales@moffat.com.au

Western Australia Telephone +61 8-9413 2400 wasales@moffat.com.au

New Zealand Moffat Limited

Christchurch 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz

Auckland Telephone +64 9-574 3150 sales@moffat.co.nz





ISO9001 Quality Management SGS Standard

Designed and manufactured by



ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection. ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice

© Copyright Moffat Ltd AN.TFN.S.1901







